



EGGER HOME 7

EGGER HOME FLOORING

7/31 Classic V4 Classic

TECHNICAL DATASHEET

COREBOARD	HDF swell stopp plus
PROFILE	The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP1 441 087 and EP 1 462 587
GUARANTEE DOMESTIC AREA	15 years according to Egger Guarantee
GUARANTEE COMMERCIAL AREA	5 years according to Egger Guarantee
ANTISTATIC PROPERTIES ACCORDING TO EN1815	Yes, <2 kv
CLASS USE	31
EUROPEAN NORM EN13329	 EN 13329-31
BOARD INFORMATION	
FORMAT	Classic
DIMENSIONS mm [length x width]	1292 X 192
COMPLETE THICKNESS	7
BEVEL	
PACK INFORMATION	
PIECES/PACK	10
m ²	2.48m ²
Kg	15.69
CLASSIFICATION AND GENERAL REQUIREMENTS ACCORDING EN13329	
ABRASION RESISTANCE ACCORDING EN13329, annex E	AC3(lp≥2000)
IMPACT RESISTANCE ACCORDING EN13329, annex H	Big ball: ≥500mm Small ball: ≥8 N
RESISTANCE TO STAINING EN438	Group 1 + 2: level 5 Group 3: level 4
EFFECT OF FURNITURE LEG ACCORDING TO EN424	No damage shall be visible, when tested with foot Type 0 artefact
EFFECT OF CASTOR CHAIR ACCORDING TO EN425 (Type W)	No change in appearance or damage
THICKNESS SWELLING ACCORDING TO ISO24336	≤18%
TOLERANCE OF TOP LAYER ACCORDING TO EN13329	Length ±0.5mm Width ±0.1mm Thickness ± 0.5mm
LIGHT FASTNESS ACCORDING EN13329	Grey scale ≥level 4(EN:20105-A02)
STATIC INDENTATION BY CONSTANT PRESSURE ACCORDING TO EN 13329	<0.01
SURFACE SOUNDNESS ACCORDING EN13329, annex D	≥1,0 N/mm ²
THERMAL RESISTANCE ACCORDING TO EN12667	0.07m ² K/W

